

Department of School & Mass Education, Govt. Of Odisha



Implementation of e Vidyalaya Project in 4000 Govt. & Govt. aided Schools of Odisha

This is to certify that the following items/Human Resources have been duly delivered and installed/deployed in our school and all equipment/items are in proper condition for implementation of ICT lab with following details.

IMP	Please tick whichever is applicable																		
IL&FS Educ																			
Telecomn	nunicati	ion Cosu	ıltants lı	ndia Ltd	1														
	UI	DISE CODE					2	1	1	2	0	9	0	4	0	0	1		
Date								4	0	2	2	0	V	4					
School Name	C	++	t	N	T	A	M	A	N	1		B	1	D	Y	A	P		
Vell	K	W	+	A	1	-	-		1.0	0							_		
Village		A	M	A	1	A	D	1	H	A	190						_		
Block	N	A	R	A	2	1	N	G	H	4	U	R							
District	C	U	T	7	A	C	K		1975										
Address	A	T	1	P	0	-	K	A	M	A	L	A	D	1	H	A			
77 F5											Pin:								
Name of Head Master/ Mistress(HM)	D	A	M	0	D	A	R		S	A	H	0	U						
HM Contact No.	8	8	9	5	8	9	ч	6	2	6									
Name of School Coordinator	m	A	u	S	u	m	E	E		D	A	S	H						
School Coordinator's Contact no.	9	7	7	6	7	6	6	4	6	5									
Implementation partner's School Code	0	D	2	3	-	C	U	T	A	-	0	9	1	5					
Room Dimension (In feet)	Length:		2:	2	1			Breadth:	11	16	,	The	3			Please Tick			
Sr. no.	Ma	Item	del	Qty.	Specification & Serial No.												Please Tick		
; · · n ·		Desktop Acer Make		1	expand	dachtecture 3.2 Ghz or higher Processor with 4 dedicated cores, RAM 4GB or higher dable to 16GB, 500 GB HDD, 19-inch or Higher LED Monitor, Built-in audio, 300 Watt op Speaker, DVD Writer,10/100/1000BaseT Ethernet, 104 Key Keyboard and Optical Mouse With at least 2 Free Full Height PCI slots,													
9		Serial no.			U	X	V	8	5	S	1	0	1	9	D	5	2		
					7	3	5	8	2										
		top(Stand Acer Make	8.70	520	expand	lable to 1	.6GB, 500 er, DVD W	GB HDD, riter,10/	19-inch 100/1000	or Higher DBaseT E	4 dedicate r LED Mor thernet, 1	oltor, Bui	ilt-in aud	dio, 300	Watt	Please Tick			
2		Serial no.		1	U	X	V	8	5	2	1	0	1	8	D	5	2		
					7	2	a	5	4	27									

	U DISE CODE				2			2	0	9	0	4	0	0	2		
3	Shared Computing Device N-computing	2	single h Card, Vi Mouse a CAT6 ca exceed cable w environ host PC	o Shared Computing Devices per Desktop. Multibox device which allows 6 users to share a gle host PC through a share computing PC-Sharing kit (which includes one full height PCI d, Virtualization software, access devices with speaker output, PS/2 uses and PS/2 Keyboard output. SVGA Monitor output and RJ45 Connection Port. with 5 f6 cables (each of 5 meters length)), Power consumption of each access device should not eed more than 1-2watts. The access device should be integrated with Host PC via CAT 6 lie with support up to 10mtr/32ft. Each user should have independent desktop dirronment. User experience on shared terminal should be substantially the same as on the it PC (Boot time, Login Experience, Responsiveness (Mouse, Keyboard, application start-up it execution), Graphics/Multimedia, Logout.										Pleas	se Tick		
	Monitor		connect	ivity with (horizon	LED Mon matt bla tal/verticergy Star	ack finish cal), wall	, brightne mounting	ess 250 c	d/m2, vie	wing an	gle 170	degrees/	160	300,650	se Tick		
	Serial no.		Pls. fill the serial no.s of all the 12 Monitors														
	1		M	M	_	Y	6	S	5	0	1	4	3	4	4		
	1		0	4	C	3	8	8	5	1	0						
	2		M	M	L	Y	7	S	S	0	1	4	3	4	3		
	2		1	6	8	4	7	8	5	1	O						
	3		M	M	L	X	K	S	2	0	1	4	3	4	5		
	3		0	A	B	6	8	4.	2	0	4						
	4		M	M	L	y	6	S	S	0	1	4	3	y	3		
	4		-	6	3	9	B	8	5)	0						
	9		M	M	1	Y	G	S	5	0	1	4	3	4	4		
8	5 igt		0	8	2	5	8	8	5	1	0						
4		12	M	M	L	Y	6	S	3	0	1	4	3	4	3		
	6		1	· 6	7	8	4	8	5	1	0						
	_			M	M	L	X	K	2	S	0	1	4	3	9	5	
	7		0	8	C	B	1	4	2	0	4			-			
	-		M	M	L	Y	6	S	S	0	1	4	3	4	4		
	8				0	4	C	4	B	8.	5	1	0				-
			M	M	L	Y	6	S	S	Q	1	y	3	4	3		
	9		1	6	3	7	8	8	5)	0						
			M	M		Y	6	S	S	0	1	4	3	4			
	10		0	4	D	2	9	8	5	1	0	2.			'		
			M	M	4	×	k	5	S	0	1	4	3	4	5		
	11		0	8	D	0	3	4	2	0	4						
			M	M	L	Y	6	S	5	0	1	4	3	4	4		
	12		0	4	D	2	5	8	5	1	0						
5	Web Cam Brand (Pis. tick) Wipro	1		MP came	era, Suppo	ort for HI			80 X 720	pixels),	Built-in i	mic with	noise	Please Tick			
6	Headphones	40					Headpl	hone witl	n Mic					Please Tick			
7	Headphone Sharer	10	5-Way 3.5-mm Headphone Splitter											Please Tick			

						1.0									
	U DISE CODE	, a			2	1	1	2	0	9	6	14	0	0	1
8	Integrated Computer Projector K-YAN	1	Specification: Projection System: DLP Technology; Brightness: 2500-ANSI Lumens (Short Throw) Resolution: SVGA (800x600); Contrast Ratio: 2500:1 Computer System: X86 architecture, 3.2GHz or higher with 4 dedicated Cores, Minimum 4MB L3 Cache, Compatible chipset with HD graphics, 4GB DDR3 RAM expandable to 16 GB, 500 GB Serial SATA II 7200 RPM HDD, Optical Drive DVD RW, Wireless Keyboard & optical Scroll Mouse. OS: DOS; Input: PS/2 Mouse & Keyboard, RF –in for TV, USB ports, Microphone in; Output: Internal 30 watts Audio Output, LAN: 1x Gbps LAN, Integrated analogue cable TV tuner.												
	Serial no.		1	3	L	GIC	2 2	20	0)	2	1	12	9	1
9	Interactive White Board Smart	1	Active A approxi Aspect I mainter isopropropratii support consum USB cable fo Electron Data Po Pota Po Vol. So without palm tou specific and facili applicati into eacl facility. A	Area: Minimately 32 Ratio: 4:3. Ratio: 4:3	2767 × 327 28. Board Sure 27. Board Sure 28. Compating 29.	ve area 15/67 rface: Durriface:	able Hard lry-erase in tem: Win Tools: Bot mechanic mA at 5 V outers. Te d other ex n (full-spi e version c online fo ne commit comaticall / Linux* orange; snap sst supply con work a orm 100 to	chooated simarkers and dows XP in finger a call and barial and manager and m	teel surfaind easily SP3, Windon desily SP3, Windon de la control de la	ce, optimolece, optimolece, optimolece, optimolece, optimolece, er from the chnology 2.0). Storing softwares and should have trues, reto collaive others of the collaive of th	ized for with white as SP2 to out any selection out and selection	projection teboard con ter Windows special too potions: Pro- puter through the project of file lication on access the rupdate vers to their active fea active fea active fea tion, focu external cut.	leaner or is 7 ols, ower ugh the from es in a CD or software ria a r tures like s to ontent upply an directly		ase Tick
10	Multi Function Printer		(best): L Processo 10/100E	Jp to 600 or speed: Base-T Et	x 600 dp Minimus hernet ne	it technol ii (1200 d m 400 Mi	pi effect dz, Conne ort, RJ-11	rive), Dispectivity, so Telephon file form	play: at le tandard: ne port, nat: JPE	ast 2-lin Hi-Spee Duplex p	d USB 2	ed		Pleas	se Tick
	Brand (Pis. tick) Ricoh	1	and unc	ompressi	ed), PDF,	GIF, BMP	, Scan re	solution,	optical:	ob to 12	00 dpi,	Certified	by IDC.		
	(Pls. tick)	1	and unc	ompress	ed), PDF,	GIF, BMP	, Scan re	solution,	B	O to 12	00 dpi,	Certified	by IDC.		
11	(Pls. tick) Ricoh	1	ISO 9001 Pure sine Battery t UPS and tempera sine waw	L Certifie e wave, E type : Sea Cabling. ture: 0 to	d. Online Efficiency aled. Mai With DG	UPS of 2 90 % or b ntenance Set comp	KVA with petter on Free, M	30 minu	ites power li load, In roller Ba	er backu put Pow sed Dou	p, Outpo	ut Wave I or > 0.90, version O z, operati	Form -	Pleas	e Tick
11	(Pis. tick) Ricoh Serial no. On Line UPS		ISO 9000 Pure sinu Battery to UPS and tempera	L Certifie e wave, E type : Sea Cabling. ture: 0 to	d. Online Efficiency aled. Mai With DG	UPS of 2 90 % or b ntenance Set comp	KVA with petter on Free, M	30 minu	ites power li load, In roller Ba	er backu put Pow sed Dou	p, Outpo	ut Wave I pr > 0.90, version O	Form -	Pleas	e Tick
	Serial no. On Line UPS Delta		ISO 9001 Pure sine Battery t UPS and tempera sine way	L Certifie e wave, I type: Se: Cabling. ture: 0 to e output	d. Online efficiency aled. Mai With DG 50 degree	UPS of 2 90 % or t ntenance Set comp ees celciu	KVA with oetter on Free, M aatibilities, noise le	30 minurated fuicro Contess, freque	tes power li load, In roller Ba ency ranguer the go	or backu put Pow sed Dou e 50+/- overnme	p, Outpi yer Factoble Cons 6% hert: nt norm	ut Wave I or > 0.90, version O z, operati	Form - nline ng t: pure	Please	J
11	Serial no. On Line UPS Delta Serial no.		ISO 9001 Pure sine Battery t UPS and tempera sine way	L Certifie e wave, I type: Se: Cabling. ture: 0 to e output	d. Online efficiency aled. Mai With DG 50 degree	UPS of 2 90 % or t ntenance Set compees celciu	KVA with oetter on Free, M aatibilities, noise le	30 minurated fuicro Contess, freque	tes power li load, In roller Ba ency ranguer the go	or backu put Pow sed Dou e 50+/- overnme	p, Outpi yer Factoble Cons 6% hert: nt norm	tut Wave I por > 0.90, version O z, operati	Form - nline ng t: pure	W	J
	Serial no. On Line UPS Delta Serial no. Networking		ISO 9001 Pure sine Battery t UPS and tempera sine way	L Certifie e wave, E type : Sec Cabling. ture: 0 to re output Jumanage chilon pri	d. Online Efficiency aled. Mai With DG to 50 degro	UPS of 2 90 % or t ntenance Set compees celciu	KVA with operation of Free, M operational size of the	30 minurated fuicro Contes, frequeevel: as p	ttes power li load, In roller Bancy ranguer the go	er backu put Pow sed Doul e 50+/- (overnme	p, Outpi pp, Outpi yer Factoble Conn 5% hert: nt norm	ut Wave I por > 0.90, version O z, operati ss. output	Form - Inline Ing It: pure	W	J Pe Tick

	U DISE CODE				2			12	0	9		9	0	0	2	
14	Servo Stabilizer Protect	1	5KVA (1 Phase Servo Motor Operated Line Voltage Corrector), Input Range: : 50V-270V (Single Phase), Mounting: On Wheels. Output range: 220V/230V/240V single phase (adjustable), earthing terminals, overload cutoff, output protection through MCB, Frequency range: 50+/- 3% hertz. Operating temperature: 0 to 50 degrees celsius.													
Serial no.			1	6	0	1	1	4	0	-8	5		E			
	Silent Generator Set Champ			ISO 9001 Certified, Minimum 3 KVA Petrol/Diesel based silent generator set with Safe Cabling and Installation												
15	Serial no.		5	1	3	t	1	0	3	0	O	5	6	1		
16	Initial meter reading of the Silent Generator Set	eading of the									Please Tio					
17	Earthing (as per IS specifications)	in the second se										Please	Tick			
18	Lighting (ISI mark)	4	40W Tub	e Light w	ith Elect	ronic Ch	oke (ISI n	nark)						Please	Tick	
19	Ceiling / Wall mounted fans (ISI mark)	48" blade with regulator, 3 Blade Indicative Brands: Philips / Wipro/ Usha /Crompton Greaves /Khaitan /Bajaj/ Havells												Please	Tick	
20	Exhaust fans (ISI mark)	2	300mm sweep, 45 Watts, Speed 1330 RPM Indicative Brands: Philips / Wipro/ Usha/Crompton Greaves /Khaitan /Bajaj / Havells												Tick	
		15	5 A- 240 V switches												Tick	
21	Switches and sockets (ISI Mark)	15	2 in 1 5A and 15A Sockets													
	little,	2	15 A – 240 V socket with shutter													
		2	Indicative Brands: - Anchor / Havells / crabtree /Wipro /Phillips / Legrand Switches and sockets is to be provided for all electronics/IT equipments including printer and Projection System to be placed at lab technician table.													
22	Computer Table Tajpuria	13	Dimensions Width 1200mm x Depth 609mm x Height 750mm 18mm pre laminated particle board conforming IS: 12823. Pretreated & powder coated steel frame. Good quality PVC edge bending to be provided on pre laminated board. No Sharp corners, smooth edges are essential. Legs frame made of 1.5 inch square pipe, 16 gauges. Table rests on good quality glide screws. Full length footrest is to be provided. One 65mm diameter hole for drawing cables is to be provided , this hole has to be covered with steel cover Good quality telescopic slider along with full width keyboard with 30cm projected depth panel, keyboard free space is 10 cm. Table must have a modesty panel of 200mm height to be provided. End caps to be provided. BIFMA Certified												Tick	
23	Chair Uma Plastic/Moderna	41	Armless Moulded Chairs, Cream colour, IStandard Compliant											Please 1	Tick	
24	Electrical meter Initial reading)0													
25	Painting	a 142	The surface OMSM are of standa	id shall be	e applied	with 2	coats of	d, shall be primer an MSM.	prepare d then w	d to the ith 2 coa	satisfact ats of dis	tion of Ol temper p	KCL / paint	Please 1	rick	
26	Lab Cleanliness Kit	1 set	Dusting cl one Foot	oth, hand mat	d held va	cuum cle	eaner, Du	ist cloth c	overs for	all the	T equipr	nents and	d	Please 1	Tick	
27	Curtains	Full lab	To mainta	in prope	r darkne	ss in the	Lab / Cla	ssroom d	uring Pro	jection				Please	Tick	
28	Wall Clock	1	ISI Mark,	Wall Cloc	k									Please T	Tick	
29	Notice Board	1	5feet x 3f	eet, P/F 1	5 thk Pir	nup boar	d with fa	abric wrap	ped all a	round				Please T	lck	
30	White Board	1	4 ftx3 ft m	ninimum :	18mm th	ickness	white bo	ard						Please T	Tick	

*** Please note that all the three signatures are mandetory on all the sheets.

****All fields are to be filled up mandatorily.

BHUB ANAME AND SET

Signature of OKCL Representative with Seal

Signature of School and Massimistress with Seal
Chintamani Bidyapitha
Kamaladiha