

Department of School & Mass Education, Govt. Of Odisha



Implementation of e Vidyalaya Project in 4000 Govt. & Govt. aided Schools of Odisha

This is to certify that the following items/Human Resources have been duly delivered and installed/deployed in our school and all equipment/items are in proper condition for implementation of ICT lab with following details.

| IMPLEMENTATION PARTNER IL&F5 Education & Technology Services Ltd. | | | | | | | | Please tick whichever is applicable | | | | | | | | | | | |
|--|---------|------------------------|----|--------|---|-----------|----------------------------|-------------------------------------|------------------------|---|-----------------------|-------------------------|-----------------------|-----------|------|------|---------|--|--|
| | | | | | | | | | | | | | | | | | | | |
| | UE | ISE CODE | | | | | 2 | 1 | 1 | 2 | 1 | 1 | 0 | 6 | 8 | 0 | 1 | | |
| Date | | | | | | | | 1 | 0 | 7 | 2 | 0 | 1 | 4 | | | | | |
| School Name | J | A | M | A | R | A | i i | U. | 9. | 3 | H | I | G | H | | | | | |
| Village | 5 | A | M | A | R | A | | | 112 | | | | | | | | | | |
| Block | N | I | S | C | H | I | N | T | A | K | 0 | I | L | I | | | | | |
| District | C | U | T | T | A | C | K | | | | | | | | | | | | |
| Address | A | T | _ | J | A | M | A | R | A | | | | | | | | | | |
| | P | 0 | _ | B | A | G | 7+ | U | N | I | | | | | | | | | |
| Name of Head Master/ | K | A | N | A | K | A | | M | A | N | J | A | R | I | | | | | |
| Mistress(HM) | 2 | A | 5 | H | | 4 | 0 | 9 | | - | | | | | | | | | |
| HM Contact No. | 9 | 7 | 7 | 7 | 0 | 2 | 1 | 8 | 0 | 6 | | | | | | | | | |
| Name of School Coordinator | P | R | A | N | A | T | 1 | | P | R | A | B | H | A | | | | | |
| School Coordinator's | 8 | A | K | A 8 | N | 5 | 7 | 6 | 3 | 1 | | | | | | | | | |
| Contact no. Implementation partner's School Code | 0 | D | て | 3 | - | C | U | T | A | - | a | 9 | 3 | 6 | | | | | |
| Room Dimension (in feet) | Length: | | 2 | 4 | 4 | | Breadth: 16 | | | | | | | | | | se Tick | | |
| Sr. no. | - N | Item | | Qty. | 1 1 | 3(1) | Specification & Serial No. | | | | | | | | | | se Tick | | |
| 1 | | Desktop Acer Mak | | 1 | X86 Architecture 3.2 Ghz or higher Processor with 4 dedicated cores, RAM 4GB or higher expandable to 16GB, 500 GB HDD, 19-inch or Higher LED Monitor, Built-in audio, 300 Watt Desktop Speaker, DVD Writer, 10/100/1000BaseT Ethernet, 104 Key Keyboard and Optical Mouse With at least 2 Free Full Height PCI slots. | | | | | | | | 0 Watt | | | | | | |
| | | Serial no | o. | | U | X | V | 8 | 5 | S | I | 0 | 1 | 9 | E | 2 | 3 | | |
| S 0 9 | | | | | 6 | 2 | 1 | 8 | 2 | | | | | | 1 | Plea | se Tick | | |
| | De | sktop(Star Acer Mal | | | exp | andable t | o 16GB, 5 aker, DVI | 00 GB HI Writer,1 | OD, 19-ind 0/100/10 | essor with th or High 000BaseT st 2 Free F | er LED M Ethernet, | lonitor, E , 104 Key | Built-In au Keyboa | udio, 300 | Watt | ~ | | | |
| 2 | * | | 0. | 1 | U | X | V | 8 | 5 | S | I | 0 | 1 | 8 | E | 2 | C | | |
| | | | | 45 05 | 3 | 8 | 9 | 4 | 0 | | | 100 | | 141 | | | | | |

| | U DISE CODE | | 2 1 1 2 1 1 0 6 | 3 0 1 Please Tick |
|---------|--|------|--|--------------------------|
| 3 | Shared Computing Device N-computing | 2 | Two Shared Computing Devices per Desktop Multibox device which allows 6 users to share single host PC through a share computing PC-Sharing kit {which includes one full height PCI Ca Virtualization software, access devices with speaker output, PS/2 Mouse and PS/2 Keybo: output. SVGA Monitor output and RJ45 Connection Port, with 5 CAT6 cables (each of 5 met length)). Power consumption of each access device should not exceed more than I-2watts. Taccess device should be integrated with Host PC via CAT 6 cable with support up to 10mtr/3. Each user should have independent desktop environment. User experience on shared termi should be substantially the same as on the host PC (Boot time. Login Experience, Responsiven (Mouse, Keyboard, application start-up and execution), Graphics/Multimedia, Logout. | e a a rd, rd ers he ft. |
| 4- ii . | Monitor | | 19-inch or higher LED Monitor with static contrast 1000:1, resolution of 1440 x 900 and V connectivity with matt black finish, brightness 250 cd/m2, viewing angle 170 degrees/ 1 degrees (horizontal/vertical), wall mounting port VDI, with Windows Certification with EPE GOLD/TCO/EnergyStarCertification | 60 |
| | Serial no. | | Pls. fill the serial no.s of all the 12 Monitors | |
| | 1 | | M M L X K 3 S 0 1 4 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 0 | 708 |
| | 2 | | MMLXKSS0143046046944209 | 801 |
| | 3 | | M M L X K S 3 0 1 4 2 0 4 | 08 |
| | 4 | | M M L X K S S 0 1 4 4 0 4 0 8 4 4 2 8 4 | 0 8 |
| | 5 | | MMLXKSS0149 040D94204 | 08 |
| 4 | 6 | 12 | M M L X K S S 0 2 4 4 0 4 0 A A 4 2 0 4 | 08 |
| | 7 | 25 1 | MM AX KS S O 1 4 4 0 4 6 9 B 4 2 0 4 | 08 |
| | 8 | -77 | M M L X K S S O 14 4 0 4 0 B E 4 \$ 0 4 | 08 |
| | gar 9 | 6 | MMLXK350144 040694204 | 68 |
| | 10 | | M M L X K S S 0 2 4 9 | 108 |
| | 11 | | M M L X K S S O 1 4 4 5 6 4 6 4 2 0 4 | 08 |
| | 12 | | MMLXKS 50 24 4 0 F 7 C & 4 2 0 4 | b F |
| 5 * | Web Cam Brand (Plz. tick) Wipro Headphones | 1 40 | Min 5MP camera, Support for HD Video calling (1280 x 720 pixels), Built-in mic with noise reduction Headphone with Mic | Please Tick Please Tick |
| 0 | rieaupitories | 40 | rieadphone with Mic | |

| | | | _ | | 0 | - dan | | 2 | | | | 0 | 0 | 0 | _ | | |
|----|--|---|--|-------------------------------------|-------------------------------------|---------------------------------------|---|---|--------------------------------------|--------------------------------------|----------------------------------|---------------------------------------|--|-----------|-------------|--|--|
| 8 | Specification: Projection System: DLP Technology:Brightness: 2500-ANSI Lumens (Short Throw) Resolution: SVGA(800x600); Contrast Ratio: 2500:1 Computer System: X86 architecture, 3.2GHz or higher with 4 dedicated Cores, Minimum 4M 1.3 Cache, Compatible chipset with HD graphics, 4GB DDR3 RAM expandable to 16GB, 500 GB Serial SATA II 7200 RPM HDD, Optical Drive DVD RW, Wireless Keyboard & optical Scroll Mouse. OS: DOS; Input: PS/2 Mouse & Keyboard, RF -in for TV, USB ports, Microphone in; Output: Internal 30 watts Audio Output, LAN: 1x Gbps LAN, Integrated analogue cable TV tuner. | | | | | | | | | | | Ple | ease Tick | | | | |
| | Serial no. | 0 | 1 | A | A | 9 | C : | 2 8 | 00 | 1 | 2 | 3 | 3 | 5 | 9 | | |
| 9 | Interactive White Board Smart | 1 | product updating service that can automatically scan for new updates and alert users to their availability. Must support Windows* / Linux* operating systems. Should have interactive features palm touch, image gallery, image enlarge; snap shots, recording lectures, reveal option, focus to specific part of content, zoom etc. Must supply additional software to collaborate external content and facilitate teachers to create new content a and manage and deliver other content. Must supply application for remote collaboration to work on the same content simultaneously and write directinto each other's documents. Minimum 100 to maximum 500 user can concurrently use the facility. Accessories: Stylus/ Pens, USB Cable, Software CD, user manual etc. to be a part of standar supply. Warranty: 5 years warranty. | | | | | | | | | | eaner or is 7 pols, power ugh the rom es in a CD or software ia a r tures like s to pontent pply an directly | ~ | Please Ticl | | |
| | Serial no. | | | | | | | 4 | | | | | | | | | |
| 10 | Multi Function Printer Brand (Pls. tick) Ricoh | Processor speed: Minimum 400 MHz, Connectivity, standard: Hi-Speed USB 2.0 port, 10/100Base-T Ethernet network port, RJ-11 Telephone port, Duplex printing: Automatic Scanner type: Flatbed, ADF, Scan file format: JPEG, TIF (compressed and uncompressed), PDF, GIF, BMP, Scan resolution, optical: Up to 1200 dpi, Certified by IDC. | | | | | | | | | | | | Please Ti | | | |
| | Serial no. | | C | N | F | 8 | F | 8 | P | 6 | 9 | 2 | | | | | |
| 11 | On Line UPS Delta Serial no. | 1 | sine wav Sealed. N With DG | e, Efficier Maintena Set comp | ncy 90 % once Free, patibilities | or better o Micro Co s, frequen | on rated for ntroller Back cy range 5 | 0 minutes ull load, Inpased Doub 60+/* 6% homent norm | out Power le Conver ertz, oper | r Factor > sion Onli ating tem | 0.90, Ba ne UPS a perature | ttery type nd Cablin e: 0 to 50 | e: | Plea | ase Tick | | |
| | Networking | | | | | | | CAT-6 cal | bling (in | casing ca | aping) fo | or all the | nodes, | Plea | ase Tick | | |
| 12 | | | Mutilifu | cntion p | rinters, P | rojection | system. | D | B | 0 | 0 | 1 | 6 | 2 | 8 | | |
| * | Serial no. | 1-24 | iv t | 1.30 | 1. 1. 8. | 14/2 | 1.1 | | | | | | | | | | |
| è | | | | | | | | | | | | | | | | | |
| 13 | Fire Extinguisher | 1 | | Portabl | e Carbon | Dioxide | Handhel | ld fire exti | inguisher | rs as per | IS specif | ication | | Pleas | se Tick | | |

| | U DISE CODE | | | 2 | 1 | 1 | 2 | 1 | 1 | 0 | G | 8 | 0 | 1 | |
|----|--|----------|--|-----------|------------|-------------|-----------|-----------|-------------|----------|----------|---|---------|---------|--|
| 14 | Servo Stabilizer Protect | 1 | SKVA (1 Phase Servo Motor Operated Line Voltage Corrector), input Range:: S0V-270V (Single Phase;, Mounting: On Wheels Output range: 220V/230V/240V single phase (adjustable), earthing terminals, overload cutoff, output protection through MCB, Frequency range: 50+/- 3% hertz. Operating temperature: 0 to 50 degrees celsius. | | | | | | | | | | | | |
| | Serial no. | | 29 | 0 | 1 | 2 | 4 | 0 | 7 | 3 | | | | | |
| | Silent Generator Set Champ | | ISO 9001 Certified, Minimum 3 KVA Petrol/Diesel based silent generator set with Safe Cabling and Installation | | | | | | | | | | | | |
| 15 | Serial no. | 1 | 51 | 3 | 2 | I | 6 | 3 | 4 | 1 | 7 | 6 | 1 | - | |
| 16 | Initial meter reading of the Silent Generator Set | | | - (| 0 | 15 | | | | | | | Plea | se Tick | |
| 17 | Earthing (as per IS Copper plate earthing stations making earthing with copper earth plate specifications) | | | | | | | | | | | ~ | se Tick | | |
| 18 | Lighting (ISI mark) | 4 | 40W Tube Light | with Elec | ctronic C | hoke (ISI | mark) | | | | | | Plea | se Tick | |
| 19 | Ceiling / Wall mounted fans (ISI mark) | 2 | 48" blade with regulator, 3 Blade Indicative Brands: Philips / Wipro/ Usha /Crompton Greaves /Khaitan /Bajaj/ Havells | | | | | | | | | | | | |
| 20 | Exhaust fans (ISI mark) | 2 | 300mm sweep, 45 Watts, Speed 1330 RPM Indicative Brands: Philips / Wipro/ Usha /Crompton Greaves /Khaitan /Bajaj / Havells | | | | | | | | | | | | |
| 21 | Switches and sockets (ISI mark) | 15 | 5 A- 240 V switches | | | | | | | | | | | | |
| | | 15 | 2 in 1 5A and 15A Sockets | | | | | | | | | | | | |
| | | 2 | 15 A - 240 V socket with shutter | | | | | | | | | | | | |
| | | | Indicative Brands: - Anchor / Havells / crabtree /Wipro /Phillips / Legrand Switches and sockets is to be provided for all electronics/IT equipments including printer and Projection System to be placed at lab technician table. | | | | | | | | | | | | |
| 22 | Computer Table Tajpuria | 13 | Dimensions Width 1200mm x Depth 609mm x Height 750mm 18mm pre laminated particle board conforming IS: 12823. Pretreated 8t powder coated steel frame. Good quality PVC edge bending to be provided on pre laminated board. No Sharp corners, smooth edges are essential. Legs frame made of 1.5 inch square pipe, 16 gauges. Table rests on good quality glide screws. Full length footrest is to be provided. One 65mm diameter hole for drawing cables is to be provided, this hole has to be covered with steel cover Good quality telescopic slider along with full width keyboard with 30cm projected depth panel, keyboard free space is 10 cm. Table must have a modesty panel of 200mm height to be provided. End caps to be provided. BIFMA Certified | | | | | | | | | | | | |
| 23 | Chair Uma Plastic/Moderna | 41 | Armless Moulde | d Chairs, | Cream co | oloui, star | ndard Co | mpliant | | | | | Plea | se Tick | |
| 24 | Electrical meter Initial reading | | 1 | 0.0 | | - | | | | | | | E . | | |
| 25 | Painting | | The surface of W OMSM and shall standard make a | be appli | ed with 2 | coats of | primer a | | | | | | Plea | se Tick | |
| 26 | Lab Cleanliness Kit | 1 set | Dusting cloth, ha | and held | vacuum d | leaner. D | ust cloth | covers fo | r all the I | T equipn | nents an | d | Plea | se Tick | |
| 27 | Curtains | Full lab | To maintain prop | oer darkn | ess in the | e Lab / Cla | assroom | during Pr | ojection | | | | - | se Tick | |
| 28 | Wall Clock | 1 | ISI Mark, Wall Cl | ock | 11 | | | | | | | | Plea | se Tick | |
| 29 | Notice Board | 1 | 5 feet x 3 feet, P | /F 15 thk | Pinup bo | ard with | fabric wr | apped all | around | 9 75 | | | Plea | se Tick | |
| 30 | White Board | 1 | 4 ftx3 ft minimu | m 18mm | thicknes | s white b | oard | | | | 140 | | Plea | se Tick | |

^{***} Please note that all the three signatures are mandatory on all the sheets.
****All fields are to be filled up mandatorily.

mentation partner's

Signature of OKCI Representative with Seal

Signature of School Head Master/Mistress with Seal