

Department of School & Mass Education, Govt. Of Odisha



Implementation of e Vidyalaya Project in 4000 Govt. & Govt. aided Schools of Odisha

This is to certify that the following items/Human Resources have been duly delivered and installed/deployed in our school and all equipment/items are in proper condition for implementation of ICT lab with following details.

IMPLEMENTATION PARTNER							Please tick whichever is applicable												
cation & Technology Services Ltd. munication Cosultants India Ltd																			
nunicat	ion Cos	ultants I	India Lt	d	E														
Specific Control of the Control of t									2	1	8	0	0	9	1)			
	Date		_		1.	0	5	0	2	2	0	1	Cy			'			
B	1	N	D	71	'A	A	A	2)	N	1		G	1	R			
2	3	1	1		5		D	2	-	H	0	0	-	_	_	_			
97	A	R	A	1	1			4	P	()	D			-	-	+			
C	U	T	T	A	C	le			1						-	-			
A	T	1	P	0		Z	1	L	_	t	N	D	A	ik i					
	1	9 1	12							Pin:	7	5	9	0	3	2			
2	U	R	Y	A	M	A	H.)		B	H	0	1						
9	9	3	8	5	9	2	7	5	7										
5	A	S	m	1	N	I Å	B	1	M	A	2	I							
9	0	h	0	h	0	a	8	1	2										
0	D	Z	3	-	C	0	7	4	1	0	9	- 1-	1						
Length:		. /	2	2	2		Breadth	:/1		6	7				Please Tio				
Ma	Item ake & Mo	del	Qty.	1	Y i	Specification & Serial No.													
,	Desktop Acer Make	9	1	expand	dable to	16GB, 500 GB HDD, 19-inch or Higher LED Monitor. Built-in audio, 300 Watt													
	Serial no.			U	X	V	8	5	2	1	0	1	9	D	5	2			
				7	3	4	4	8											
				expand	able to 1	16GB, 500 er, DVD V	.6GB, 500 GB HDD, 19-inch or Higher LED Monitor, Built-in audio: 300 Watt												
			1	U	X	V	8	7	C	1	0	1	8	0	[]	2			
	B L Z N C A S O Desk	Date B J L S Date B J L S Date B J L S D D D D D D D D D D D D D D D D D D	Action & Technology Section & Technology & Tech	ation & Technology Services Launication Cosultants India Lt U DISE CODE Date B 1 N D L 3 4 Z 1 L L N A R A C U T T A T / P S U R Y 9 9 3 8 5 A S M O D Z 3 Length: 2 Item Make & Model Qty. Desktop (Stand by)	ation & Technology Services Ltd. nunication Cosultants India Ltd U DISE CODE Date B 1 N D H L 3 H 1 Z I L L 1 N A R A S C U T T A A T / P O S U R Y A 9 9 3 8 5 J A S M T U Desktop Acer Make Desktop Acer Make Name Acer Make Name N	ation & Technology Services Ltd. Funication Cosultants India Ltd U DISE CODE Date B 1 N D H Y L S H I G Z I L L I N N A R A S I C U T T A C A T / P O S U R Y A M 9 9 3 8 5 9 5 A S M I N O D D Z 3 - C Length: 22 Item Make & Model Qty. Desktop Acer Make Qty. Desktop Speak	ation & Technology Services Ltd. Punication Cosultants India Ltd U DISE CODE Date Date	ation & Technology Services Ltd. nunication Cosultants India Ltd U DISE CODE Date Date	ation & Technology Services Ltd. Junication Cosultants India Ltd U DISE CODE Date Date	Serial no. Desktop Services Ltd.	Acer Make Acer Make	Serial no. Desktop Acer Make Acer	ation & Technology Services Ltd. Dunication Cosultants India Ltd UDISE CODE Date Date	ation & Technology Services Ltd. Dunication Cosultants India Ltd UDISE CODE Date Date	ation & Technology Services Ltd. Discode	### atton & Technology Services Ltd. ### atton &			

	U DISE CODE				2	TI		12	1	8	0	0	19	4	1	
3	Shared Computing Device N-computing	Two Shared Computing Devices per Desktop. Multibox device which allows 6 users to share a single host PC through a share computing PC-Sharing kit (which includes one full height PCI Card, Virtualization software, access devices with speaker output, PS/2 Mouse and PS/2 Keyboard output. SVGA Monitor output and RJ45 Connection Port. with 5 CAT6 cables (each of 5 meters length)), Power consumption of each access device should not exceed more than 1-2watts. The access device should be integrated with Host PC via CAT 6 cable with support up to 10mtr/32ft. Each user should have independent desktop environment. User experience on shared terminal should be substantially the same as on the host PC (Boot time, Login Experience, Responsiveness (Mouse, Keyboard, application start-up and execution), Graphics/Multimedia, Logout.												se Tick		
	Monitor		19-inch or higher LED Monitor with static contrast 1000:1, resolution of 1440 x 900 and VGA connectivity with matt black finish, brightness 250 cd/m2, viewing angle 170 degrees/ 160 degrees (horizontal/vertical), wall mounting port VDI, with Windows Certification with EPEAT GOLD / TCO /Energy Star Certification													
	Serial no.					Р	ls. fill the	serial no	o.s of all t	he 12 M	onitors		.,			
	1		MO	M	L	×	K	S	2	0	1	4	3	4	5	
3				8	A	8	5	4	2	0	4					
	2		M	M		Y	6	2	2	0	1	4	3	4	3	
	16.		1	6	7	D	0	8	5	1	0					
	3		M	M	L	Y	6	S	5	0	1	4	3	4	3	
			1	6	3	D	A	8	5	1	0					
	4		M	M	L	y	6	5	5	0	1	4	3	4	3	
			-	6	7	D	9	8	5	1	0					
			M	M	1_	×	K	S	S	0	1	4	3	4	5	
			0	A	B	7	E	4	2	0	4			_		
4	6	12	M	M	2	X	K	2	5	0	1	4	3	4	5	
			0	7	E	C	7	4	2	0	4					
	7		M	M	_	Y	6	5	S	0	1	4	3	4	3	
			1	6	6	E	8	8	5	1	0					
	8		M	M	L	X	6	2	S	0	1	9	3	4	(1)	
			1	6	7	B	9	8	5	1	0					
	9		M	M	1	Y	6	2	S	0	1	4	3	y	3	
			1	6	7	9	7	8	5	1	0					
	10		M	M	L	×	K	2	S	0	t	4	3	4	5	
			0	8	A	8	7	4	2	0	4					
	11		M	M	L	X	6	2	S	0	1	4	3	4	3	
	11		1	6	6	F	D	8	5	9	0					
	12		M	M	L	X	K	S	S	0	1	4	3	4	5	
			0	A	B	3	9	4	2	0	4					
5	Brand (Pls. tick) Wipro	1	Min 5M	1P camer	a, Suppo	ort for HD		alling (12)	80 X 720	pixels), E	Built-in n	nic with	noise	Please Tick		
6	Headphones	40					Headph	one with	Mic					Please	Tick	
7	Headphone Sharer	10			_	5-Wa	y 3.5-mm	Headph	one Split	ter				Please	Tick	

8:

			-	12		2)	9	2	1 2		OT	n	0	8	,	
8	Integrated Computer Projector K-YAN	Specification: Projection System: DLP Technology; Brightness: 2500-ANSI Lumens (Short Throw) Resolution: SVGA (800x600); Contrast Ratio: 2500:1 Computer System: X86 architecture, 3.2GHz or higher with 4 dedicated Cores, Minimum 4M L3 Cache, Compatible chipset with HD graphics, 4GB DDR3 RAM expandable to 16 GB, 500 GB Serial SATA II 7200 RPM HDD, Optical Drive DVD RW, Wireless Keyboard & optical Scroll Mouse. OS: DOS; Input: PS/2 Mouse & Keyboard, RF –in for TV, USB ports, Microphone in; Output: Internal 30 watts Audio Output, LAN: 1x Gbps LAN,												Please 1			
	Serial no.		1	3	1	G	(7	0	M				4		T	
9	Interactive White Board Smart	1	Act app Asp Mail isop ope sup; cons USB cable Elect Data PC,Sc DVD. withe prod availa palm specif and fr applic into e facility	Active Size: Minimum 77" diagonal Active Area: Minimum active area 156 cm W × 117cm H Resolution: Digitizing resolution is approximately 32767 × 32767 Aspect Ratio: 4:3.Board Surface: Durable Hard-coated steel surface, optimized for projection, maintenance free, compatible with dry-erase markers and easily cleaned with whiteboard cleaner or isopropyl alcohol (IPA), Operating System: Windows XP SP3, Windows Vista® SP2 or Windows 7 operating system and Linux, Writing Tools: Both finger and pen touch without any special tools, supports multi touch and use of non mechanical and battery free objects. Power Options: Power consumption is less than 0.5 W (100 mA at 5 V). Must obtain power from the computer through the USB cable for Windows® and Linux® computers. Technology: Touch technology. No interference from Electromagnetic sources/sunlight and other external influences Data Ports: 12 Mbit /s USB connection (full-speed USB 1.1 or USB 2.0). Storage: Saving of files in PC, Software: Must include a complete version of the white boarding software application on a CD or DVD. Software must also be available online for download. Users must be able to access the software without having to register for an online community. Software must be available for update via a product updating service that can automatically scan for new updates and alert users to their availability. Must support Windows® / Linux® operating systems. Should have interactive features like palm touch, image gallery, image enlarge; snap shots, recording lectures, reveal option, focus to specific part of content, zoom etc. Must supply additional software to collaborate external content and facilitate teachers to create new content and manage and deliver other content. Must supply an application for remote collaboration to work on the same content simultaneously and write directly into each other's documents. Minimum 100 to maximum 500 user can concurrently use the supply. Warranty: 5 years warranty.											Please Tic		
Serial no	Serial no.		5	B	14	8	0	C	2	10	6	E		7	2	1 8	
										_	1	-	,				
10	Multi Function Printer Brand (Pis. tick) Ricoh	1	Proces 10/100 Autom	: Up to 18 Up to 600 ssor speed: DBase-T Et natic Scann acompresse	Minimu hernet ne	m 400 M etwork po	Hz, Conn	tive), Dis ectivity, 1 Teleph	splay: at I standard one port,	east 2-lir l: Hi-Spee , Duplex p	orinting:			c.	Please	Tick	
10	Multi Function Printer Brand (Pis. tick)	1	Proces 10/100 Autom	ssor speed: OBase-T Et	Minimu hernet ne	m 400 M etwork po	Hz, Conn	tive), Dis ectivity, 1 Teleph	splay: at I standard one port,	east 2-lir l: Hi-Spee , Duplex p	orinting:			c.	Please	Tick	
10	Multi Function Printer Brand (Pis. tick) Ricoh	1	ISO 900 Pure sir Battery UPS and temperature	ossor speed: OBase-T Et natic Scann	Minimu hernet ne ler type: ed), PDF,	uPS of 21	KVA with petter on Free, Mi patibilities, noise le	a 30 minu	isplay: at I standard one port, rmat: JPE , optical:	least 2-lir l: Hi-Spee , Duplex p G, TIF (cc Up to 12 Per backup nput Pow sed Doub	o, Outpu	ed Certified at Wave r > 0.90, ersion O	Form -		Please Til	3	
5.	Multi Function Printer Brand (Pis. tick) Ricoh Serial no.		ISO 900 Pure sir Battery UPS and temperature	Dase-T Et latic Scann locompresson locompres	Minimu hernet ne ler type: ed), PDF,	uPS of 21	KVA with petter on Free, Minathilities	a 30 minu	isplay: at I standard one port, rmat: JPE , optical:	least 2-lir l: Hi-Spee , Duplex p G, TIF (cc Up to 12 Per backup nput Pow sed Doub	o, Outpu	ed Certified at Wave r > 0.90, ersion O	Form -			3	
11	Multi Function Printer Brand (Pls. tick) Ricoh Serial no. On Line UPS Delta	1	ISO 900 Pure sir Battery UPS and temperations was	Dase-T Et latic Scann locompresson locompres	Minimum hernet neier type: ed), PDF, J. Online fficiency led. Main With DG 50 degree	ups of 21 UPS of 21 90 % or battenance Set complete celciu	KVA with petter on Free, Minatibilities, noise le	n 30 minu rated fu icro Cont	isplay: at I standard one port, cone port, c	least 2-liris Hi-Speeis Hi-Speeis Duplex Duplex G, TIF (cc. Up to 12	o, Outpuer Factoriale Convey % hertz, nt norms	ed Certified It Wave or > 0.90, ersion O operati s. output	Form -			ck	
s.	Multi Function Printer Brand (Pls. tick) Ricoh Serial no. On Line UPS Delta Serial no.	1	ISO 900 Pure sir Battery UPS and temperations was	Dase-T Etiatic Scannicompresson Compresson Capting Cap	Minimum hernet neier type: ed), PDF, J. Online fficiency led. Main With DG 50 degree	ups of 21 UPS of 21 90 % or battenance Set complete celciu	KVA with petter on Free, Minatibilities, noise le	n 30 minu rated fu icro Cont	isplay: at I standard one port, cone port, c	least 2-liris Hi-Speeis Hi-Speeis Duplex Duplex G, TIF (cc. Up to 12	o, Outpuer Factoriale Convey % hertz, nt norms	ed Certified It Wave or > 0.90, ersion O operati s. output	Form -		Please Th	ck	
11	Multi Function Printer Brand (Pis. tick) Ricoh Serial no. On Line UPS Delta Serial no. Networking Serial no.	1	ISO 900 Pure sir Battery UPS and tempera sine was	Dase-T Etiatic Scannicompresson Compresson Capting Cap	Minimum hernet neier type: ed), PDF, d. Online fficiency led. Main With DG 50 degree	UPS of 21 90 % or bettenance Set competes celcius BIT switce lection sy	KVA with petter on Free, Minatibilities, noise left, with Crystem.	an 30 minus rated full icro Continues, freque evel: as p	iplay: at I standard one port, mat: JPE one port, mat: JPE one port of the por	least 2-lir is: Hi-Spee is: Hi-Spee is: Hi-Spee is: Hi-Spee is: Duplex is	o, Outpuer Factorole Convey % hertz, nt norms	at Wave r > 0.90, ersion 0, operatis. output	Form - , noline ing t: pure	8	Please Th	ck	

	U DISE CODE				2			12		8	0	0	9		1	
14	Servo Stabilizer Protect	1	5KVA (1 Phase Servo Motor Operated Line Voltage Corrector), Input Range:: 50V-27 (Single Phase), Mounting: On Wheels. Output range: 220V/230V/240V single phase (adjustable), earthing terminals, overload cutoff, output protection through MCB, Frange: 50+/- 3% hertz. Operating temperature: 0 to 50 degrees celsius.											Plea	se Tic	
	Serial no.		,	6	0	1	1	4	0	7	8					
	Silent Generator Set Champ		ISO 9001 Certified, Minimum 3 KVA Petrol/Diesel based silent generator set with Safe Cabling and Installation													
15	Serial no.	1	5	1	3	1	1	0	2	9	1	7	1	~	/	
16	Initial meter reading of the Silent Generator Set		00082												se Tie	
17	Earthing (as per IS specifications)		Copper plate earthing stations making earthing with copper earth plate												se Ti	
18	Lighting (ISI mark)	4	40W Tube Light with Electronic Choke (ISI mark)												se/Ti	
19	Ceiling / Wall mounted fans (ISI mark)	2	48" blade with regulator, 3 Blade Indicative Brands: Philips / Wipro/ Usha /Crompton Greaves /Khaitan /Bajaj/ Havells												se Tie	
20	Exhaust fans (ISI mark)	2	300mm sweep, 45 Watts, Speed 1330 RPM Indicative Brands: Philips / Wipro/ Usha /Crompton Greaves /Khaitan /Bajaj / Havells												se Tie	
	15	5 A- 240 V switches												e Tie		
21 Switc	Switches and sockets (ISI Mark)	15	2 in 1 5A and 15A Sockets													
	, water	2	15 A – 240 V socket with shutter													
			Indicative Brands: - Anchor / Havells / crabtree /Wipro /Phillips / Legrand Switches and sockets is to be provided for all electronics/IT equipments including printer and Projection System to be placed at lab technician table.													
22	Computer Table Tajpuria	13	Dimensions Width 1200mm x Depth 609mm x Height 750mm 18mm pre laminated particle board conforming IS: 12823. Pretreated & powder coated steel frame. Good quality PVC edge bending to be provided on pre laminated board. No Sharp corners, smooth edges are essential. Legs frame made of 1.5 inch square pipe, 16 gauges. Table rests on good quality glide screws. Full length footrest is to be provided. One 65mm diameter hole for drawing cables is to be provided it is to be provided. Side along with full width keyboard with 30cm projected depth panel, keyboard free space is 10 cm. Table must have a modesty panel of 200mm height to be provided. BiFMA Certified												se Tio	
23	Chair Uma Plastic/Moderna	41	Armless Moulded Chairs, Cream colour, IStandard Compliant											Pleas	e Pic	
24	Electrical meter Initial reading		007.2													
25	Painting	_	The surface of Wall and Ceiling to be painted, shall be prepared to the satisfaction of OKCL / OMSM and shall be applied with 2 coats of primer and then with 2 coats of distemper paint of standard make as approved by OKCL / OMSM.											Please Tic		
26	Lab Cleanliness Kit	1 set	Dusting o	loth, han	d held v	acuum c	leaner, D	ust cloth	covers fo	r all the I	T equipn	nents and	d	Please	tic	
27	Curtains	Full lab	To maint	ain prope	er darkne	ess in the	Lab / Cl	assroom	during Pr	ojection				Pleas	Tic	
28	Wall Clock	1	ISI Mark,	Wall Clo	ck		4							Please Tic		
29	Notice Board	1	5feet x 3	feet, P/F	15 thk P	inup boa	rd with 1	fabric wra	pped all	around				Please	The	
30	White Board	1	4 ftx3 ft i	minimum	18mm t	hickness	white bo	pard						Heast	Tic	

*** Please note res are mandetory on all the sheets.

Signature of OKCL Representative with Seal