Department of School & Mass Education, Govt. Of Odisha



Implementation of e Vidyalaya Project in 4000 Govt. & Govt. aided Schools of Odisha

This is to country that the following items/Human Resources have been duly delivered and installed/deployed in our school and all equipment/items are in proper condition for implementation of ICT lab with following details.

F	IMPLE	Please tick whichever is applicable																		
\vdash	IL&F5 Educat					-		سما												
\vdash	Telecommu																_			
卜	U DISE CODE									2	7		0	0	4	2	O	4		
t								2	_3	0	4	2	0	1	5					
	School Name	র্ভা	O	٧	丁	U	র্জা	++]	ত্য	H	5	C	1-1	0	0	1_			
				<u>-</u>				_	,		· .					_		<u></u>		
	Village	ব্য	U	L	Ų	M	Ų	N	D	A		:	<u> </u>							
	Block	R.	Ą	M	A	Ŋ	A	ৰ্জ	U	D	A									
<u> </u>	District	R	Α	Y	A	ৰ্	A	D	A			<u> </u>					<u> </u>			
	Address	Ø	U	L	U	М	U	7	D.	A,						·	_			
		ŋ	I	S	T		R	A	Y	A	Gr	A	D	A	-	<u> </u>				
	Name of Head Master/	5	L	A	1_	1	7	A		K	U	M	A	R	1			-		
	Mistress(HM)		<u> </u>			<u> </u>				<u> </u>	<u> </u>		<u> </u>		<u> </u>		ļ <u>.</u>			
	HM Contact No.	8	7	6	3_	6	2	3	3	6	8			<u> </u>			-	<u> </u>		
	Name of School Coordinator	S	A	T	7	A	17	Α	R	4	7	A	7	<u> </u>	S	A	H			
+	School Coordinator's Contact no.	8	0	9	3	5	6	6	2		0									
ļ	Implementation partner's School Code	0	D	ス	6	-	R	A	γ	A	<u> </u>	3	4	7	8	<u> </u>	01-1	ise Tick		
1	Room Dimension (in feet)	Length	:	 -	2	20		Breadth: 20												
Î	Sr. no.	ħ	Item Vake & Mo	odel	Qty.		Specification & Serial No.										Please Tick			
		Desktop Acer Make				X86 Architecture 3.2 Ghz or higher Processor with 4 dedicated cores, RAM 4GB or higher processor with 4 dedicated cores, RAM 4GB or higher LED Monitor, Built-in audio, 300 Desktop Speaker, DVD Writer, 10/100/1000BaseT Ethernet, 104 Key Keyboard and Ol Mouse With at least 2 Free Full Height PCI slots.										IO Watt	Watt j			
	1			1	تا	×	V	F	1	S	1	3	2	8	F	1	1			
		Serial no.				5	9	9	O	8					<u> </u>			<u> </u>		
		Desktop(Stand by) Acer Make				ext	andabie t	o 16GB, l aker, DVI	500 GB H D Writer,	igher Prod 100, 19-in 10/100/1 Vith at lea	ich or Hig 000BaseT	her LED N Ethernet	//onitor, (, 104 Ke	Built-in a y Keyboa	udio, 30	0 Watt	Please Tick			
	2	2			1	U	X	V	F	T	S	1	3	2	7	F	1	1		
		Serial no.				5	9	8	1	7						<u> </u>				

	A DISE CODE		··	· · · · · · · · ·		211	ĺ	7	7]	I = I) 7	5 7		71	O[I]							
3	Shared Computing Device N-computing		Virtu outp 2 leng acce Each shou	Jalization out. SVGA th)). Powe ss device oser should be subs	software Monitor or consur should be uld have stantially	g Devices a share co b, access of output arm potion of a integrate independ the same lication sta	onr Dest imputing devices with RIAS Co each acco ed with H ent deski as on the	ctop Mul PC-Sham ath spea onnection ess device ost PC via op environ host PC in	tibox deving kit (which ker output in Port, which is should a CAT 6 conment. It is should in the cat it is should in the cat it is should in the cat is should be cat in the ca	ice which included in PS/2 lith 5 CA hot excellable with the point of	h allows des one f Mouse a f6 cables ed more is support erience o	iull heigh and PS/2 (nach o than I-2s tup to 16 or shared	to share t PC+Car Keyboa f 5 mete watts, Th Imitr/32(a d, rd rs ne t.	arcase Tile							
	Monitor		19-inch or higher LED Monitor with static contrast 1000:1, resolution of 1440 x 900 and VGA connectivity with matt black finish, brightness 250 cd/m2, viewing angle 170 degrees/ 160 degrees (horizontal/vertical), wall mounting port VDI, with Windows Certification with EPEAT GOLD/TCO/Energy Star Certification																			
	Serial no.		Pls. fill the serial no.s of all the 12 Monitors																			
	1		М	M	1	У	6	 		0		14	-4	4	8							
		\dashv	0	3	12	- A	12	- 8			3	 	<u> </u>	<u> </u>	<u> </u>							
	2		N	M 3	6	<u>y</u> 2	6	<u>5</u>	<u>5</u>	0	3	14	14	14	8							
		٦	M	M	L	Тy	6	S	2	10	1	14	4	14	8							
	3		0	3	2	A	Ĭ	8	5	ĻŤ.	3	+ '	+-	 '	18							
		7	N	M	1	У	6	5	S	0	1	4	4	A	8							
	•		O	3	5	19	6	8	5	1	3	 	 	1	10							
	5		N	M	L	Y	6	S	S	G	1	14	4	1	8							
		_	O	3	1	5	12	8	5	1	3											
4	6	12	M	14	L	У	6	S	5	O	1	4	1	4	8							
			0	3	2	9	В	8	5	1	3				 - -							
			М	И	L	У	6	3	S	0	1	4	4	4	8							
]	0	3	5	A	6	8	5	1	3											
	8		M	17	L	Y	б	5	3	Q	1	4	4	1	g							
			Ö	3	1	5	3	8	5	1	3											
	9		N	* 4	L	γ	E	5	S	Q	1	4	4	4	8							
		-	0	3	1	.5	Œ	8	5	1	3			,								
	10	}	M	И	<u>L</u>	У	6	5	3	O	1	4	4	4	B							
		İ	0	2	E	6	0	8	5	1	3											
	. 11		И	М	<u>L</u>	٧	6	3	S	Ø		4	4	4	8							
			O	3	5	A	Q	8	5	1	3											
	12		М	M	<u>L</u>	Y	6	5	3	0	1	4	4	4	8							
	Web Cam	-	0	3	2	A	4	8	5)	3	[1	ł								
5	Brand (etc. tick) Wipro	1	Min 5ħ	AP camer	a, Suppo	rt for HD	Video cal	ling (128 luction	0 x 720 p	ixels), B	 illt-in mi	ic with n	aise	Please	Tick							
6 	Headphones	40												Please	Picasa Jick							
	Headphone Sharer	_ 10				5-Way	3.5-mm i	leadpho	ne Splitte	r	Headphone with Mic 10 5-Way 3.5-mm Headphone Splitter											

1	U DISE CODE				2	17	12	17	1	0	Io	4	12	10	$\tilde{I}\tilde{I}$
8	integrated Computer Projector K-YAN	1	Specification . Projection System: DLP Technology:Brightness: 2500 ANSI Lumens (Short Throw) Resolution : SVGA(800x600): Contrast Ratio :2500:1 Computer System : X86 architecture, 3.2GHz or higher with 4 dedicated Cores, Minimum 4MB 1.3 Cache. Compatible chipset with HD graphics, 4GB DDR3 RAM expandable to 16GB.												
	Serial no.		1	4	A	G (0	10	1	12	3	9	7	5
9	Interactive White Board Smart	1	Active Size: Minimum 77" diagonal Active Area: Minimum active area 156 cm W x 117cm H Resolution: Digitizing resolution is approximately 32767 x 32767 Aspect Ratio: 4:3.8oard Surface: Durable Hard-coated steel surface, optimized for projection, maritenance free, compatible with dry-erase markers and easily cleaned with whiteboard cleaner of isopropyl alcohol (IPA), Operating System: Windows XP SP3, Windows Vista* SP2 or Windows 7 operating system and Linux, Writing Tools: Both finger and pen touch without any special tools, supports multi touch and use of non mechanical and battery free objects. Power Options: Power consumption is less than 0.5 W (100 mA at 5 V). Must obtain power from the computer through the USB cable for Windows* and Linux* computers. Technology: Touch technology. No interference from Electromagnetic sources/sunlight and other external influences Data Ports: 12 Mbit / s USB connection (full-speed USB 1.1 or USB 2.0). Storage: Saving of files in PC, Software: Must include a complete version of the white boarding software application on a CD of DVD. Software must also be available online for download. Users must be able to access the software.											Ples	se Tro
	Serial no.		3	13	1	8	10	C	2	0	6	4	6	†	_
10	Multi Function Printer Brand (Pls. tick) Ricoh	1	Mode: Up to 18 ppm, Print technology: Laser, Print quality black (best): Up to 600 x 600 dpi (1200 dpi effective), Display: at least 2-line LCD, Processor speed: Minimum 400 MHz, Connectivity, standard: Hi-Speed USB 2.0 port, 10/1008ase-T Ethernet network port, RJ-11 Telephone port, Duplex printing: Automatic Scanner type: Flatbed, ADF, Scan file format: JPEG, TIF (compressed and uncompressed), PDF, GIF, BMP, Scan resolution, optical: Up to 1200 dpi, Certified by IDC.												sa Tick
	Serial no.		C	7	F	8	F	B	B	C	丁	L			
11	On Line UPS Delta	1	ISO 9001 Certified. Online UPS of 2KVA with 30 minutes power backup, Output Wave Form - Pure sine wave, Efficiency 90 % or better on rated full load, Input Power Factor > 0.90, Battery type : Sealed. Maintenance Free, Micro Controller Based Double Conversion Online UPS and Cabling. With OG Set compatibilities, frequency range 50+/* 6% hertz, operating temperature: 0 to 50 degrees celcius, noise level: as per the government norms, output: pure sine wave output												sa Tick
	Serial no.		3	2	.5	1	3_	C	<u>G</u>	,3	E	6	8	W	ユ
	Networking					GABIT swi		CAT-6 cat	l oling (in c	asing ca	ping) for	r all the r	nodes,	Pleas	se Tick
12	Serial no.		Q	ج5_	5	H	7	D	B	0	0	0	/	7	7
13	Fire Extinguisher	1			e Carbo	n Dioxide	L Handheld	fire exti	nguishers	as per l	S specifi	cation		Please	r Tick
	Expiry Date		2	0	2	14	1	ł	1	l	l			\ \	_

	. Siss gode				2		12	7	. 	0	0	1.4	a	0		.3 .			
14	Servo Stabilizer Profect	1	SKVA (1 Phase Servo Motor Operated High Moltage Corrector), input Range: 1507-2107 (Single Phase), Mounting, On Wheels Discourting: 2207/2307/2407 single phase (adjustable), earthing terminals, overload out of, oxput protection through MUB, Frequency sange: 501/-3% hertz, Operating temperature, Bito, 50 degrees colorus.																
	Serial no.	,	P	1	0	8	1	4	0	5	0	0_	2	6	2	-			
	Silent Generator Set	1)1 Certifi and Ins	ed, Minim tallation	ലം 3 KV	'A Petrol,	i - <u></u> folesolib	ased sile:	n; genera	otor set	wrter Sai	i c	Plear	Ar Yile				
15	Serial no.	1	H	0	0	0	0	7	0	7				`	/				
16	Initial meter reading of the Slient Generator Set		0036																
17	Earthing (as per 15 specifications)		Copper	Please Tick															
18	Lighting (ISI mark)	4	40W Tu	ı	rase Fick														
19	Celling / Wall mounted fans (ISI mark)	2	48" blac /Cromp	Pleas															
20	Exhaust fans (ISI mark)	2	300mm sweep, 45 Watts, Speed 1330 RPM Indicative Brands: Philips / Wipro/ Usha /Crompton Greaves /Khaitan /Bajaj / Havells																
		15	5 A- 240 V switches]			
21	Switches and sockets	15	2 in 1 5A and 15A Sockets																
	(ISI mark)	2																	
			Indication Switche printer																
22	Computer Table Tajpuria	13	Dimensi conform to be pre- made o footrest has to b with 300 of 200m	ng ne th kle rd															
23	Chair Uma Plastic/Moderna	41	Armless	Moulde	d Chairs, (Cream co	loui, stan	dard Corr	pliant					Pleas	ie Tick				
24	Electrical meter Initial reading				5.1	Ī													
25	Painting		OM\$M	and shall	all and Co be applie s approve	d with 2	coats of p	rimer an	, ,					Please Tick					
26	Lab Cleanliness Kit	1 set	Dusting one Foo		nd held v	ecuum c	eaner. Ou	ist cloth o	overs for	ali the fi	Γ equipπ	ients an	d	Pleas	Please Tick				
27	Curtains	Full lab	To maintain proper darkness in the Lab / Classroom during Projection											Pleas	Please Tick				
28	Walt Clock	1	iSi Mark	, Wall Cl	ock									Picas	e Tick				
29	Notice Board	1	5 feet x	3 feet, P,	/F'15 thk	Pinup bo	ard with f	abric wra	pped ali	around				1	æ Yirk				
30	White Board	1	4 îtx3 ft	minimu	m 18mm	thickness	white bo	ard						Meas	Mease Tick				

^{***} Please note that all the three signatures are mandatory on all the sheets.
****All fields are to be filled up mandatorily.

